

Notes:

1. Color: Black;
2. Male(M3) Torques: $\cong 0.13 \text{ N}\cdot\text{m}$;
3. Male(M4) Torques: $\cong 0.3 \text{ N}\cdot\text{m}$;
3. Male(M5) Torques: $\cong 0.58 \text{ N}\cdot\text{m}$;
4. RoHS Compliant.

Part No.	Article No.	Material	M Thread	A	B	C
42436	GHTS-MM-M3-6-5B-HB	PA66 UL94 HB	M3	5.0	6.0	6.0
42359	GHTS-MM-M3-6-6B-HB			6.0		
42552	GHTS-MM-M3-6-5B	5.0				
42553	GHTS-MM-M3-6-6B	6.0				
41295	GHTS-MM-M3-6-25B	25.0				
42924	GHTS-MM-M3-6-35B	35.0				
42925	GHTS-MM-M4-6-12B	PA66 UL94 V2	M4	12.0	6.0	6.0
42926	GHTS-MM-M4-6-25B			25.0		
42927	GHTS-MM-M4-6-40B			40.0		
43582	GHTS-MM-M5-10-80B		M5	80.0	10.0	10.0

Gecko International Co.

DATE

2021-11-18

DIMENSION

TOLERANCE

TITLE

HEX SPACER

SCALE

FIT

L \leq 4

± 0.10

ARTICLE NO.

GHTS-MM

MOLD NO.

S0417

DRAW

JF

UNIT

MM

4 < L \leq 15

± 0.20

PART NO.

SEE TABLE

MATERIAL

SEE TABLE

DESIGN

JF

VERSION

A0

15 < L \leq 50

± 0.30

DWG NO.

E4078


COLOR

SEE NOTES

APPROVAL

FDL

VIEW



50 < L \leq 100

± 0.40